

Technical Data Sheet

Fibro Seal® Primer

Roofing

7 Day Technical Support 1800 655 711

Testing Approvals: N/A

Description

Fibro Seal® Primer is a waterborne penetrating treatment to weathered asbestos cement sheeting that soaks through the lichen and degraded asbestos down to sound base material, binding these unstable elements. When used together with **Crommelin Fibro Seal® Topcoat**, the product forms part of the **Crommelin Fibro Seal® System**, a proven encapsulation system used throughout Australia since 1990.

Features and Benefits

- Bind weathered asbestos cement sheet fibres
- Waterborne

Areas of Use

- Weathered asbestos cement products

Technical Data

Number of Coats:	1	Curing time:	7 days
Spreading Rate Per Coat:	3m ² /L	Colour:	Clear
Wet Film Per Coat:	330 microns	Thinner:	N/A
Recoat (@25°C):	2 hours	Shelf Life:	12 months

Application Guide

Surface Preparation

- Remove large lumps of lichen and moss growth manually and clean loose growth away with an approved industrial vacuum cleaner.
- Assess the degree of weathering of the asbestos fibres by applying a length of self adhesive tape to the surface. Adhere completely and then pull off in one swift motion. This is used as a basis to determine the amount of **Fibro Seal® Primer** required.

Application Procedure and Equipment

- Apply the specified flood coat of **Fibro Seal® Primer** using spray, brush or roller.

Reassess the complete binding of the asbestos fibres by the **Fibro Seal® Primer** using a self adhesive tape "pull off test". If fibres appear on the adhesive surface apply a 2nd coat. Reassess.

Precautions

- Ensure all requirements applicable to the relevant state Occupational Health and Safety legislation are complied with.
- When working on weathered asbestos roofs, refer to NOHSC Codes of Practice 2018 (2005) Management and Control of Asbestos in Workplaces.

Cleaning

- Clean equipment with water before product dries.

Technical Data Sheet

Fibro Seal[®] Primer

Roofing

7 Day Technical Support 1800 655 711

Health and Safety

Safety Precautions

- Avoid contact with skin and eyes.
- If product is splashed on skin it should be washed off with water before it can dry.
- Wear suitable protective clothing, gloves and eye protection during application.

First Aid

Swallowed: Contact a doctor or Poisons Information Centre. Do not induce vomiting. Give water to drink.
 Eye: Gently flush with running water, holding eyelids open for 15 minutes. Seek medical attention.

For detailed information refer to product label and the current Material Safety Data Sheet available from Crommelin[®].

In the case of an emergency please call the Poisons Information Centre on 13 11 26

Transport and Storage

Sizes:	15L	Flash Point:	N/A
Weights:	17Kg	UN Number:	N/A
Dangerous Goods Class:	N/A	Poisons Schedule:	5

Disclaimer

Crommelin[®] and other marks followed by [®] are registered trademarks. Marks followed by the symbol of [™] are trademarks. Any advice, recommendation, information, assistance or service provided by Crommelin[®] in relation to its products or their use is given in good faith, however is provided without responsibility or liability. Customers need to undertake their own assessment to determine the suitability of a product for the particular use intended. As the performance of any product is subject to a wide variety of different surface types as well as environmental and surface-specific conditions, it is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it performs on the specific surface.